NSN 4820-00-287-2981

Safety Relief Valve - Page 1 of 2

Thread Direction:
Right-hand 2nd end
Flow Control Device:

Bonnet Type: Inside spring

Bonnet Attachment Method:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-287-2981

Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
3 1st end
Connection Style:
Plain (pipe) 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 1st end
Connection Type:
Threaded external pipe 2nd end
Features Provided:
Bonnet packing and pressure tight outlet side
Valve Size:
0.500 inches
Maximum Operating Pressure:
100.0 pounds per square inch single response
Thread Size:
0.500 inches 2nd end
Opening Pressure Setting:
10.0 pounds per square inch
Outside Diameter:
3.562 inches 1st end
First Connection Face To Centerline Distance:
2.656 inches
Bolt Hole Diameter:
0.562 inches 1st end
Second Connection Face To Centerline Distance:
2.750 inches
Bolt Circle Diameter:
2.438 inches 1st end
Flange Face Design:
Plain 1st end

NSN 4820-00-287-2981

Safety Relief Valve - Page 2 of 2



Material:
Copper alloy
Media For Which Designed:
Air 2nd response
Style Designator:
Angle flanged ends
Thread Series Designator:
Npt 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0