

View Online at <https://aerobasegroup.com/nsn/4820-00-287-3011>

Pipe Size Accommodated:

0.750 inches all ends

Flow Control Device:

Disk

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Streamlined with two brazing rings err-100

Valve Operation Method:

Automatic or manual

Connection Type:

Unthreaded internal pipe all ends

Features Provided:

Pressure tight outlet side

Adjustable Pressure Range:

+39.0/+63.0 pounds per square inch

Maximum Operating Pressure:

400.0 pounds per square inch single response

Special Features:

Process per military specification mil-m-9950

Material:

Nickel alloy 400 seat

Material Specification:

Qq-n-288, compa federal specification single material response flow control device

Media For Which Designed:

Oxygen, gaseous single response

Style Designator:

Angle

Reference Number Differentiating Characteristics:

Special cleaning in accordance with mil-m-9950

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-m-9950 spec.