## NSN 4820-00-287-3011

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-3011

Pipe Size Accommodated:
0.750 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Connection Style:
Streamlined with two brazing rings err-100
Valve Operation Method:
Automatic or manual
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+39.0/+63.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Special Features:
Process per military specification mil-m-9950
Material:
Nickel alloy 400 seat
Material Specification:
Qq-n-288, compa federal specification single material response flow control device
Media For Which Designed:
Oxygen, gaseous single response
Style Designator:
Angle
Reference Number Differentiating Characteristics:
Special cleaning in accordance with mil-m-9950
Shelf Life:
N/a
Unit Of Measure:

## NSN 4820-00-287-3011

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-m-9950 spec.