NSN 4820-00-287-3017

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-3017

Pipe Size Accommodated:
0.500 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
86.0 pounds per hour
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Adjustable Pressure Range:
+11.0/+15.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.500 inches 2nd end
Material:
Copper alloy
Material Specification:
Qq-c-390, alloy b5/d/ federal specification single material response seat
Media For Which Designed:
Steam single response
Style Designator:
Angle
Thread Series Designator:
Npt 2nd end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-287-3017

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0