## NSN 4820-00-287-3037

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-3037

Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
10 1st end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Mounting Facility:
Bracket
Adjustable Pressure Range:
+11.0/+28.0 pounds per square inch
Outside Diameter:
9.062 inches 1st end
Thickness:
0.734 inches 1st end
<b>Bolt Hole Diameter:</b>
0.562 inches 1st end
Bolt Circle Diameter:
7.812 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
7.000 inches 1st end
Furnished Items And Quantity:
1 sight gage
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-287-3037

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0