## NSN 4820-00-287-3037

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-3037

| Flow Control Device:               |
|------------------------------------|
| Poppet                             |
| Bonnet Type:                       |
| Inside spring                      |
| Bonnet Attachment Method:          |
| Bolted                             |
| Disk Loading Method:               |
| Spring                             |
| Renewable Seat Ring Type:          |
| Threaded                           |
| Bolt Hole Quantity:                |
| 10 1st end                         |
| Valve Operation Method:            |
| Manual                             |
| Flange Shape:                      |
| Round with holes 1st end           |
| Connection Type:                   |
| Flange 1st end                     |
| Mounting Facility:                 |
| Bracket                            |
| Adjustable Pressure Range:         |
| +11.0/+28.0 pounds per square inch |
| Outside Diameter:                  |
| 9.062 inches 1st end               |
| Thickness:                         |
| 0.734 inches 1st end               |
| <b>Bolt Hole Diameter:</b>         |
| 0.562 inches 1st end               |
| Bolt Circle Diameter:              |
| 7.812 inches 1st end               |
| Flange Face Design:                |
| Raised straight 1st end            |
| Raised Face Height:                |
| 0.062 inches 1st end               |
| Raised Face Diameter:              |
| 7.000 inches 1st end               |
| Furnished Items And Quantity:      |
| 1 sight gage                       |
| Shelf Life:                        |
| N/a                                |
| Unit Of Measure:                   |

--

## NSN 4820-00-287-3037

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0