## NSN 4820-00-287-3139

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-3139

Pipe Size Accommodated:
1.000 inches 1st end
Flow Control Device:
Disk
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
93.0 pounds per hour
Maximum Operating Temp:
800.0 degrees fahrenheit single response
Minimum Operating Temp:
401.0 degrees fahrenheit
Connection Style:
Socket err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Adjustable Pressure Range:
+33.0/+55.0 pounds per square inch
Maximum Operating Pressure:
2000.0 pounds per square inch single response
Opening Pressure Setting:
50.0 pounds per square inch
Special Features:
W/lifting lever and inconel spring
Material:
Steel comp 410 stem
Material Specification:
Astm a479 assn standard single material response flow control device
Media For Which Designed:
Steam single response
Style Designator:
Angle
Specification Or Standard:
A-1 type and c class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 4820-00-287-3139

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0