NSN 4820-00-287-3212

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-3212

Pipe Size Accommodated:

0.750 inches 2nd end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Connection Style:

Plain, optional en (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Valve stem lock shield and pressure tight outlet side

Thready Qty Per Inch (tpi):

14 2nd end

Adjustable Pressure Range:

+11.0/+15.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch 3rd response

Thread Size:

0.750 inches 2nd end

Material:

Steel stem

Material Specification:

Qq-c-390 federal specification single material response seat

Media For Which Designed:

Fuel/oil, hydrocarbon 2nd response

Style Designator:

Angle

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

NSN 4820-00-287-3212

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

