NSN 4820-00-287-3332

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-3332

Thread	Class:

3a 2nd end

Thread Direction:

Right-hand 2nd end

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Maximum Operating Temp:

200.0 degrees fahrenheit single response

Connection Style:

Flared (tube) 2nd end

Valve Operation Method:

Manual

Connection Type:

Unthreaded internal tube 1st end

Mounting Facility:

Lug

Maximum Operating Pressure:

500.0 pounds per square inch single response

Thread Size:

0.875 inches 2nd end

Seat Angle:

45.0 degrees 2nd end

Outside Diameter Tube Accommodated:

0.625 inches 2nd end

Material:

Plastic polyamide flow control device

Media For Which Designed:

Refrigerant 12 1st response

Style Designator:

Straight thru

Thread Series Designator:

Unf 2nd end

Furnished Items And Quantity:

1 cap and 1 chain

Shelf Life:

N/a

Unit Of Measure:

NSN 4820-00-287-3332

Globe Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

