NSN 4820-00-287-4063

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-4063

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Maximum Operating Temp:

225.0 degrees fahrenheit single response

Minimum Operating Temp:

-40.0 degrees fahrenheit

Connection Style:

Plain (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 2nd end

Features Provided:

Valve stem lock shield and pressure tight outlet side

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.375 inches all ends

Seat Angle:

37.0 degrees 2nd end

Opening Pressure Setting:

200.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.375 inches all ends

Material:

Rubber chloroprene class cr flow control device

Media For Which Designed:

Refrigerant 12 1st response

Style Designator:

Angle

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

NSN 4820-00-287-4063

Safety Relief Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A046b0