## NSN 4820-00-287-4063

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-4063

Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Minimum Operating Temp:
-40.0 degrees fahrenheit
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 2nd end
Features Provided:
Valve stem lock shield and pressure tight outlet side
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
Seat Angle:
37.0 degrees 2nd end
Opening Pressure Setting:
200.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.375 inches all ends
Material:
Rubber chloroprene class cr flow control device
Media For Which Designed:
Refrigerant 12 1st response
Style Designator:
Angle
Thread Series Designator:
Nptf 1st end
Shelf Life:
N/a

## NSN 4820-00-287-4063

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

