NSN 4820-00-287-4072

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-4072

Pipe Size Accommodated:
0.375 inches 2nd end
Thread Class:
3a 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
225.0 degrees fahrenheit 2nd response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 2nd end
Features Provided:
Valve stem lock shield and pressure tight outlet side
Thread Size:
0.375 inches 1st end
Seat Angle:
45.0 degrees 1st end
Opening Pressure Setting:
200.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Material:
Rubber chloroprene class cr flow control device
Media For Which Designed:
Refrigerant 12 1st response
Style Designator:
Angle
Thread Series Designator:
Unf 2nd end
Shelf Life:
N1/-

N/a

NSN 4820-00-287-4072

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0