NSN 4820-00-287-4264

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-4264

Pipe Size Accommodated:
0.500 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Retaining screw
Maximum Operating Temp:
550.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic or manual
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Valve stem lock shield and pressure tight outlet side
Maximum Operating Pressure:
250.0 pounds per square inch single response
Thread Size:
0.500 inches 2nd end
Opening Pressure Setting:
250.0 pounds per square inch
Material:
Nickel alloy flow control device
Media For Which Designed:
Steam single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-287-4264

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0