## NSN 4820-00-287-4622

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-4622

| Pipe Size Accommodated:                               |
|---|
| 0.500 inches 2nd end                                  |
| Thread Direction:                                     |
| Right-hand 1st end                                    |
| Flow Control Device:                                  |
| Disk or stem  |
| Bonnet Type:  |
| Inside spring   |
| Bonnet Attachment Method:                             |
| Threaded  |
| Disk Loading Method:                                  |
| Spring  |
| Connection Style:                                     |
| Plain, optional en (pipe) 1st end                     |
| Valve Operation Method:                               |
| Automatic or manual                                   |
| Connection Type:                                      |
| Threaded internal pipe 2nd end                        |
| Features Provided:                                    |
| Valve stem lock shield and pressure tight outlet side |
| <b>Maximum Operating Pressure:</b>                    |
| 132.0 pounds per square inch single response          |
| Thread Size:  |
| 0.500 inches 2nd end                                  |
| Opening Pressure Setting:                             |
| 132.0 pounds per square inch                          |
| Special Features:                                     |
| As differentiated by pressure                         |
| Material:   |
| Steel stem  |
| Media For Which Designed:                             |
| Air single response                                   |
| Style Designator:                                     |
| Angle   |
| Thread Series Designator:                             |
| Npt 1st end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                      |
|   |
| Demilitarization:                                     |

No

## NSN 4820-00-287-4622

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0