NSN 4820-00-287-4675

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-4675

| Thread Class: |
|---|
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Integral |
| Disk Loading Method: |
| Spring |
| Connection Style: |
| Gasket sea (boss) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal boss 1st end |
| Mounting Facility: |
| Threaded fastener |
| Features Provided: |
| Bonnet packing |
| Thready Qty Per Inch (tpi): |
| 18 1st end |
| Adjustable Pressure Range: |
| +2300.0/+3850.0 pounds per square inch |
| Maximum Operating Pressure: |
| 3850.0 pounds per square inch single response |
| Thread Size: |
| 0.562 inches 1st end |
| Opening Pressure Setting: |
| 3400.0 pounds per square inch |
| Media For Which Designed: |
| Hydraulic fluid, petroleum base single response |
| Surface Treatment: |
| Anodize |
| Style Designator: |
| Angle w/offset |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 4820-00-287-4675

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

