

View Online at <https://aerobasegroup.com/nsn/4820-00-287-5538>

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

9 1st end

Maximum Operating Temp:

650.0 degrees fahrenheit 4th response

Valve Operation Method:

Manual

Flange Shape:

Round 1st end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Valve Size:

4.000 inches

Maximum Operating Pressure:

350.0 pounds per square inch 1st response

Outside Diameter:

9.250 inches 1st end

Face To Face Distance:

15.000 inches

Thickness:

0.938 inches 1st end

Bolt Hole Diameter:

0.812 inches 1st end

Bolt Circle Diameter:

7.688 inches 1st end

Flange Face Design:

Plain 1st end

Special Features:

First end style designator: plai (l1) ; end connection quantity: 2; second end relationship with first: identical;

Material:

Steel uns j03008 body

Media For Which Designed:

Fuel/oil, hydrocarbon 1st response

Style Designator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0