NSN 4820-00-287-5643

Angle Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-287-5643

Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Renewable Seat Ring Type:
Pressed-in
Bolt Hole Quantity:
4 1st end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Features Provided:
Valve stem lock shield and bonnet packing
Valve Size:
1.500 inches
Maximum Operating Pressure:
600.0 pounds per square inch single response
Outside Diameter:
6.125 inches 1st end
0.120 monoc for one
Thickness:
Thickness:
Thickness: 0.875 inches 1st end
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance:
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches Bolt Hole Diameter:
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches Bolt Hole Diameter: 0.812 inches 1st end
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches Bolt Hole Diameter: 0.812 inches 1st end Second Connection Face To Centerline Distance:
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches Bolt Hole Diameter: 0.812 inches 1st end Second Connection Face To Centerline Distance: 5.750 inches
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches Bolt Hole Diameter: 0.812 inches 1st end Second Connection Face To Centerline Distance: 5.750 inches Bolt Circle Diameter:
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches Bolt Hole Diameter: 0.812 inches 1st end Second Connection Face To Centerline Distance: 5.750 inches Bolt Circle Diameter: 4.500 inches 1st end
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches Bolt Hole Diameter: 0.812 inches 1st end Second Connection Face To Centerline Distance: 5.750 inches Bolt Circle Diameter: 4.500 inches 1st end Flange Face Design:
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches Bolt Hole Diameter: 0.812 inches 1st end Second Connection Face To Centerline Distance: 5.750 inches Bolt Circle Diameter: 4.500 inches 1st end Flange Face Design: Raised straight 1st end
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches Bolt Hole Diameter: 0.812 inches 1st end Second Connection Face To Centerline Distance: 5.750 inches Bolt Circle Diameter: 4.500 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height:
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches Bolt Hole Diameter: 0.812 inches 1st end Second Connection Face To Centerline Distance: 5.750 inches Bolt Circle Diameter: 4.500 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.250 inches 1st end
Thickness: 0.875 inches 1st end First Connection Face To Centerline Distance: 4.750 inches Bolt Hole Diameter: 0.812 inches 1st end Second Connection Face To Centerline Distance: 5.750 inches Bolt Circle Diameter: 4.500 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.250 inches 1st end Raised Face Diameter:

NSN 4820-00-287-5643

Angle Valve - Page 2 of 2

A046b0



Media For Which Designed:
Steam single response
Style Designator:
Angle flanged ends
Reference Number Differentiating Characteristics:
As differentiated by type c40
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: