

View Online at <https://aerobasegroup.com/nsn/4820-00-287-5643>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Pressed-in

Bolt Hole Quantity:

4 1st end

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Features Provided:

Valve stem lock shield and bonnet packing

Valve Size:

1.500 inches

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outside Diameter:

6.125 inches 1st end

Thickness:

0.875 inches 1st end

First Connection Face To Centerline Distance:

4.750 inches

Bolt Hole Diameter:

0.812 inches 1st end

Second Connection Face To Centerline Distance:

5.750 inches

Bolt Circle Diameter:

4.500 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

2.875 inches 1st end

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

Reference Number Differentiating Characteristics:

As differentiated by type c40

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A046b0