NSN 4820-00-287-5661



Stop-check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-287-5661 **Thread Direction:** Right-hand all ends **Flow Control Device:** Disk **Bonnet Type:** Outside screw-yoke **Bonnet Attachment Method: Bolted Disk Loading Method:** Spring Renewable Seat Ring Type: Threaded **Maximum Operating Temp:** 200.0 degrees fahrenheit single response **Connection Style:** Plain, optional end (pipe) all ends **Valve Operation Method:** Manual **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Features Provided:** Bonnet packing Thready Qty Per Inch (tpi): 11-1/2 all ends **Maximum Operating Pressure:** 500.0 pounds per square inch single response **Thread Size:** 1.500 inches all ends Material: Copper alloy 955 flow control device **Material Specification:** Qq-b-671, class 4-cancelled federal specification single material response flow control device Media For Which Designed: Water, fresh single response **Style Designator:** Angle **Thread Series Designator:** Npt all ends

N/a

Shelf Life:

NSN 4820-00-287-5661

Stop-check Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A530b0