NSN 4820-00-287-5679

Stop-lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-5679

Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 1st end
Maximum Operating Temp:
850.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round 1st end
Connection Type:
Flange 1st end
Mounting Position:
Horizontal
Features Provided:
Bonnet packing
Maximum Operating Pressure:
600.0 pounds per square inch single response
Outside Diameter:
6.500 inches 1st end
Face To Face Distance:
11.500 inches
Thickness:
1.000 inches 1st end
Bolt Hole Diameter:
0.688 inches 1st end
Bolt Circle Diameter:
5.000 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
3.625 inches 1st end
Material:
Stainless steel stem
Media For Which Designed:

Steam single response

NSN 4820-00-287-5679

Stop-lift-check Valve - Page 2 of 2



	nator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0