NSN 4820-00-287-5942

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-5942

Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 1st end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Mounting Position:
Horizontal or vertical
Features Provided:
Bonnet packing
Valve Size:
1.000 inches
Maximum Operating Pressure:
600.0 pounds per square inch single response
Outside Diameter:
4.875 inches 1st end
Face To Face Distance:
8.500 inches
Thickness:
0.688 inches 1st end
Bolt Hole Diameter:
0.688 inches 1st end
Bolt Circle Diameter:
3.500 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
2.750 inches 1st end
Material:
Steel body
Media For Which Designed:

Steam single response

NSN 4820-00-287-5942

Stop-check Valve - Page 2 of 2



Style	De	sia	nato	١r٠
OLYIC	De.	oig:	IIau	<i>,</i> ,

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0