NSN 4820-00-287-6037

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-6037

Pipe Size Accommodated:

1.000 inches 2nd end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

123.0 cubic feet per minute

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) 2nd end

Valve Operation Method:

Automatic or manual

Connection Type:

Threaded internal pipe 2nd end

Features Provided:

Pressure tight outlet side

Maximum Operating Pressure:

300.0 pounds per square inch single response

Thread Size:

1.000 inches 2nd end

Opening Pressure Setting:

60.0 pounds per square inch

Material:

Copper alloy

Media For Which Designed:

Acetylene single response

Style Designator:

Angle

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

NSN 4820-00-287-6037

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

