## NSN 4820-00-287-6037

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-6037

Pipe Size Accommodated:
1.000 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
123.0 cubic feet per minute
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic or manual
Connection Type:
Threaded internal pipe 2nd end
Features Provided:
Pressure tight outlet side
Maximum Operating Pressure:
300.0 pounds per square inch single response
Thread Size:
1.000 inches 2nd end
Opening Pressure Setting:
60.0 pounds per square inch
Material:
Copper alloy
Media For Which Designed:
Acetylene single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

## NSN 4820-00-287-6037

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0