NSN 4820-00-287-6051



Globe valve - Page 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/4820-00-287-6051	
Flow Control Device:	
Disk	
Bonnet Type:	
Outside screw-yoke	
Bonnet Attachment Method:	
Bolted	
Renewable Seat Ring Type:	
Threaded	
Bolt Hole Quantity:	
4 all ends	
Maximum Operating Temp:	
406.0 degrees fahrenheit 1st response	
Valve Operation Method:	
Manual	
Flange Shape:	
Round with holes all ends	
Connection Type:	
Flange all ends	
Features Provided:	
Bonnet packing	
Valve Size:	
2.500 inches	
Maximum Operating Pressure:	
200.0 pounds per square inch 2nd response	
Outside Diameter:	
7.000 inches all ends	
Face To Face Distance:	
8.500 inches	
Thickness:	
0.688 inches all ends	
Bolt Hole Diameter:	
0.750 inches all ends	
Bolt Circle Diameter:	
5.500 inches all ends	
Flange Face Design:	

Plain all ends

Material:

Iron cast uns f12102 body

Material Specification:

Astm b62 assn standard single material response seat

Media For Which Designed:

Water-oil-gas 2nd response

NSN 4820-00-287-6051

Globe Valve - Page 2 of 2



Sty					

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0