## NSN 4820-00-287-6074

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-6074
Thread Direction:
Right-hand 2nd end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Disk Loading Method:
Spring
Bolt Hole Quantity:
6 1st end
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes 1st end
Connection Type:
Threaded internal pipe 2nd end
Valve Size:
2.500 inches
Adjustable Pressure Range:
+11.0/+32.0 pounds per square inch
Maximum Operating Pressure:
100.0 pounds per square inch single response
Thread Size:
2.000 inches 2nd end
Outside Diameter:
5.062 inches 1st end
First Connection Face To Centerline Distance:
4.562 inches
Second Connection Face To Centerline Distance:
2.562 inches
Flange Face Design:

Flange Face Design:

Plain 1st end

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

## NSN 4820-00-287-6074

Safety Relief Valve - Page 2 of 2



Thread Series Designator:
Npt 2nd end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0