NSN 4820-00-287-6078

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-6078

Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 2nd end
Maximum Operating Temp:
406.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+13.0/+20.0 pounds per square inch
Maximum Operating Pressure:
100.0 pounds per square inch single response
Thread Size:
1.250 inches 1st end
Outside Diameter:
4.250 inches 2nd end
Thickness:
0.475 inches 2nd end
Bolt Hole Diameter:
0.562 inches 2nd end
Bolt Circle Diameter:
3.125 inches 2nd end
Flange Face Design:
Plain 2nd end
Special Features:
W/lifting lever

NSN 4820-00-287-6078

Safety Relief Valve - Page 2 of 2



Material:
Copper alloy
Media For Which Designed:
Steam single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0