NSN 4820-00-288-0548



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-288-0548 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit 2nd response **Connection Style:** Flareless all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Vertical Thready Qty Per Inch (tpi): 20 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.438 inches all ends Seat Angle: 24.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.250 inches 1st end Material: Steel comp 440c flow control device **Material Specification:** Qq-s-764, type 303-canceled federal specification single material response seat Media For Which Designed: Hydraulic fluid, mineral base single response **Surface Treatment: Passivate Style Designator:** Straight thru **Thread Series Designator:**

N/a

Unjf all ends
Shelf Life:

NSN 4820-00-288-0548

Check Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A530b0