## NSN 4820-00-288-6662

Fluid Pressure Regulating Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-00-288-6662



**Body Material:** Steel, corrosion resisting **Outside Surface Treatment: Passivated Body Style:** Straight thru Media For Which Designed: Air **First End Connection Type:** Threaded internal pipe First End Style Designator: Optional end First End Thread Size And Series/type Designator: 1/4-18 npt **First End Thread Direction:** Right-hand Second End Relationship With First End: Identical **Seat Material:** Steel, corrosion resisting **Flow Control Device:** Cone, bottom guided and cone, top guided Flow Control Device Material: Polyamide nylon **End Connection Quantity:** 2 Renewable Seat Ring Type: Threaded **Mounting Facility:** Flange **Outlet Pressure Range:** +0.5/+25.0 pounds per square inch **Regulation Type:** Manual single stage **Manual Control Method:** Wheel Valve Stem Design: Single seat Valve Loading Method: Spring **Remote Actuation Method:** 

Diaphragm

## NSN 4820-00-288-6662

**Fiig:** A21100

Fluid Pressure Regulating Valve - Page 2 of 2



| Maximum Inlet Pressure Rating:   |
|--|
| 1000.0 pounds per square inch  |
| Filter:  |
| Included   |
| Tempurature Rating:  |
| Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit              |
| Special Features:  |
| 10.0 cfm maximum flow capacity at maximum rated inlet and outlet pressures |
| Reference Number Differentiating Characteristics:                          |
| As differentiated by outlet pressure range and type of end connections     |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |