## NSN 4820-00-288-6886

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-288-6886

Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 1st end
Valve Operation Method:
Air
Flange Shape:
Round 2nd end
Connection Type:
Flange 1st end
Valve Size:
2.625 inches
Power Drive Operating Pressure:
634.0 pounds per square inch
Outside Diameter:
7.562 inches 2nd end
Thickness:
1.000 inches 1st end
First Connection Face To Centerline Distance:
5.500 inches
Bolt Hole Diameter:
0.687 inches 1st end
Second Connection Face To Centerline Distance:
5.062 inches
Bolt Circle Diameter:
5.000 inches 1st end
Flange Face Design:
Plain 2nd end
Raised Face Height:
0.250 inches 2nd end
Raised Face Diameter:
4.250 inches 1st end
Material:
Stainless steel stem
Style Designator:
Angle flanged ends
Reference Number Differentiating Characteristics:
Right hand valve

## NSN 4820-00-288-6886

Safety Relief Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0