NSN 4820-00-288-6892

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-288-6892

Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
8 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Valve Size:
2.000 inches
Maximum Operating Pressure:
670.0 pounds per square inch single response
Outside Diameter:
7.562 inches 2nd end
Thickness:
1.000 inches 1st end
First Connection Face To Centerline Distance:
5.500 inches
Bolt Hole Diameter:
0.812 inches 2nd end
Second Connection Face To Centerline Distance:
5.312 inches
Bolt Circle Diameter:
6.000 inches 2nd end
Flange Face Design:
Plain 2nd end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
2.625 inches 1st end
Material:
Stainless steel stem
Style Designator:
Angle flanged ends
Reference Number Differentiating Characteristics:
Left hand valve

NSN 4820-00-288-6892

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0