

View Online at <https://aerobasegroup.com/nsn/4820-00-288-6925>

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

90209.0 pounds per hour

Bolt Hole Quantity:

9 2nd end

Maximum Operating Temp:

750.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange 1st end

Adjustable Pressure Range:

+641.0/+700.0 pounds per square inch

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outside Diameter:

8.688 inches 2nd end

Thickness:

1.125 inches 1st end

Bolt Hole Diameter:

0.812 inches 2nd end

Bolt Circle Diameter:

7.125 inches 2nd end

Flange Face Design:

Plain 2nd end

Raised Face Height:

0.500 inches 1st end

Raised Face Diameter:

0.500 inches 1st end

Material:

Steel body

Media For Which Designed:

Steam single response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0