NSN 4820-00-288-7288

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-288-7288

Pipe Size Accommodated:
0.750 inches 2nd end
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
14 2nd end
Adjustable Pressure Range:
+18.0/+32.0 pounds per square inch
Maximum Operating Pressure:
100.0 pounds per square inch single response
Thread Size:
0.500 inches all ends
Material:
Nickel alloy flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Angle
Thread Series Designator:
Npt all ends
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-288-7288

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0