

View Online at <https://aerobasegroup.com/nsn/4820-00-288-7336>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

700.0 degrees fahrenheit 1st response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal or vertical

Features Provided:

Bonnet packing

Valve Size:

1.250 inches

Maximum Operating Pressure:

1000.0 pounds per square inch 2nd response

Outside Diameter:

6.125 inches all ends

Face To Face Distance:

9.500 inches

Thickness:

0.875 inches all ends

Bolt Hole Diameter:

0.875 inches all ends

Bolt Circle Diameter:

4.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches all ends

Raised Face Diameter:

2.875 inches all ends

Material:

Steel stem

Material Specification:

Astm a216, grade wcb assn standard single material response body

Style Designator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0