

View Online at <https://aerobasegroup.com/nsn/4820-00-288-7567>

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Union

**Valve Operation Method:**

Manual

**Connection Type:**

Threaded internal pipe

**Features Provided:**

Bonnet packing

**Valve Size:**

0.750 inches

**Maximum Operating Pressure And Media For Which Designed:**

125.0 pounds per square inch steam and 200.0 pounds per square inch water-oil-gas

**Thread Size:**

0.750 inches

**Stem Type:**

Rising

**Maximum Operating Temperature And Media For Which Designed:**

406.0 degrees fahrenheit steam and 150.0 degrees fahrenheit water-oil-gas

**Inlet Relationship With Outlet:**

Identical

**Material:**

Graphite seat

**Material Specification:**

Astm b-62 assn standard single material response disk

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved sources 82666 have indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Thread Series Designator:**

Npt

**Furnished Items And Quantity:**

1 handwheel

**Specification Or Standard:**

2; jst1; jcla type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500a0