

View Online at <https://aerobasegroup.com/nsn/4820-00-288-7836>

Pipe Size Accommodated:

0.500 inches 2nd end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

274.0 pounds per hour

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

450.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) 1st end

Valve Operation Method:

Automatic or manual

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Valve stem lock shield and bonnet packing and pressure tight outlet side

Adjustable Pressure Range:

+76.0/+175.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch single response

Thread Size:

0.500 inches 2nd end

Material:

Steel stem

Material Specification:

Qq-c-390, alloyd4/d/ federal specification single material response body

Media For Which Designed:

Steam single response

Style Designator:

Angle

Thread Series Designator:

Npt 1st end

Reference Number Differentiating Characteristics:

As differentiated by valve size and relief pressure range

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0