NSN 4820-00-288-9134

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-288-9134

Pipe Size Accommodated:
0.500 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Ball
Disk Loading Method:
Spring
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Plain, optional end (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
14 2nd end
Maximum Operating Pressure:
maximum operating recodure.
300.0 pounds per square inch single response
-
300.0 pounds per square inch single response
300.0 pounds per square inch single response Thread Size:
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material:
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device Media For Which Designed:
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device Media For Which Designed: Water, fresh single response
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device Media For Which Designed: Water, fresh single response Style Designator:
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device Media For Which Designed: Water, fresh single response Style Designator: Straight thru
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device Media For Which Designed: Water, fresh single response Style Designator: Straight thru Thread Series Designator:
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device Media For Which Designed: Water, fresh single response Style Designator: Straight thru Thread Series Designator: Npt 1st end
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device Media For Which Designed: Water, fresh single response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life:
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device Media For Which Designed: Water, fresh single response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device Media For Which Designed: Water, fresh single response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure:
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device Media For Which Designed: Water, fresh single response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure:
300.0 pounds per square inch single response Thread Size: 0.500 inches 2nd end Material: Plastic flow control device Media For Which Designed: Water, fresh single response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: