NSN 4820-00-288-9801



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-288-9801 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 280.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 12 1st end **Maximum Operating Pressure:** 600.0 pounds per square inch single response **Thread Size:** 1.062 inches all ends Seat Angle: 37.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.750 inches 1st end **Special Features:** Other media utilized: helium, hydrogen, hydraulic fluid (mineral base), hydrolube, lubricating oil, nitrogen Material: Rubber butadiene-acrylonitrile class nbr flow control device Media For Which Designed: Fuel/oil, hydrocarbon 2nd response **Surface Treatment:** Anodize **Style Designator:** Straight thru **Thread Series Designator:**

N/a

Unj all ends Shelf Life:

NSN 4820-00-288-9801

Check Valve - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A530b0