## NSN 4820-00-289-0672

Float Valve - Page 1 of 2

Flow Control Device:

**Bonnet Type:**Packing retaining

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-289-0672

Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
125.0 degrees fahrenheit single response
Valve Operation Method:
Hydraulic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Features Provided:
Bonnet packing
Valve Size:
4.000 inches
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
9.000 inches all ends
Thickness:
0.938 inches all ends
First Connection Face To Centerline Distance:
6.125 inches
Bolt Hole Diameter:
7.500 inches all ends
Second Connection Face To Centerline Distance:
6.125 inches
Bolt Circle Diameter:
0.750 inches all ends
Flange Face Design:
Plain all ends
Material:
Rubber chloroprene class cr flow control device
Media For Which Designed:
Water, fresh single response
Style Designator:
Angle flanged ends

## NSN 4820-00-289-0672

Float Valve - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-v-16271 government specification

**Specification Or Standard:** 

A style and 4 in. Size

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0