NSN 4820-00-289-0894

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-289-0894

Pipe Size Accommodated:
0.750 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Connection Style:
Streamlined with one brazing ring err-100
Valve Operation Method:
Automatic or manual
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+23.0/+38.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Material:
Nickel alloy flow control device
Material Specification:
Qq-c-390, alloy4/d/ federal specification single material response body
Media For Which Designed:
Fuel/oil, hydrocarbon 1st response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A046b0

NSN 4820-00-289-0894

Safety Relief Valve - Page 2 of 2



Mil-std (military Standard):

Mil-v-24332 spec.