NSN 4820-00-289-0912

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-289-0912

| Pipe Size Accommodated: |
|--|
| 0.750 inches 2nd end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Integral |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 400.0 degrees fahrenheit single response |
| Connection Style: |
| Plain, optional en (pipe) 1st end |
| Valve Operation Method: |
| Automatic or manual |
| Connection Type: |
| Threaded internal pipe 1st end |
| Features Provided: |
| Pressure tight outlet side |
| Adjustable Pressure Range: |
| +61.0/+120.0 pounds per square inch |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch single response |
| Thread Size: |
| 0.750 inches 2nd end |
| Material: |
| Steel stem |
| Material Specification: |
| Qq-c-390, alloyb5/d/ federal specification single material response body |
| Media For Which Designed: |
| Water, fresh single response |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4820-00-289-0912

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0