NSN 4820-00-289-1151

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-289-1151

| Pipe Size Accommodated: |
|---|
| 0.500 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Threaded |
| Disk Loading Method: |
| Spring |
| Connection Style: |
| Plain (pipe) 1st end |
| Valve Operation Method: |
| Automatic or manual |
| Connection Type: |
| Threaded external pipe 1st end |
| Features Provided: |
| Valve stem lock shield |
| Maximum Operating Pressure: |
| 4000.0 pounds per square inch single response |
| Thread Size: |
| 0.500 inches 1st end |
| Opening Pressure Setting: |
| 800.0 pounds per square inch |
| Material: |
| Stainless steel stem |
| Media For Which Designed: |
| Air single response |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A046b0