

View Online at <https://aerobasegroup.com/nsn/4820-00-289-1397>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

8 1st end

Maximum Operating Temp:

850.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Mounting Position:

Horizontal or vertical

Features Provided:

Bonnet packing

Valve Size:

3.000 inches

Maximum Operating Pressure:

300.0 pounds per square inch single response

Outside Diameter:

8.250 inches 1st end

Thickness:

1.250 inches 1st end

First Connection Face To Centerline Distance:

7.000 inches

Bolt Hole Diameter:

0.812 inches 1st end

Second Connection Face To Centerline Distance:

7.000 inches

Bolt Circle Diameter:

6.625 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

5.750 inches 1st end

Special Features:

Drain connection above seat

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530b0