

View Online at <https://aerobasegroup.com/nsn/4820-00-289-1518>

Flow Control Device:

Disk

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

650.0 degrees fahrenheit single response

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Valve stem lock shield

Valve Size:

0.750 inches

Adjustable Pressure Range:

+276.0/+450.0 pounds per square inch

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outside Diameter:

4.625 inches 1st end

Thickness:

0.625 inches 1st end

First Connection Face To Centerline Distance:

3.000 inches

Bolt Hole Diameter:

0.688 inches 1st end

Second Connection Face To Centerline Distance:

3.000 inches

Bolt Circle Diameter:

3.250 inches 1st end

Flange Face Design:

Plain 2nd end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

2.500 inches 1st end

Material:

Steel body

Material Specification:

Mil-s-872 military specification single material response body

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-s-872 spec.