

View Online at <https://aerobasegroup.com/nsn/4820-00-289-1523>

Flow Control Device:

Disk

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

2220.0 pounds per hour

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

775.0 degrees fahrenheit single response

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Valve stem lock shield

Adjustable Pressure Range:

+25.0/+40.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

6.625 inches all ends

Thickness:

0.500 inches all ends

First Connection Face To Centerline Distance:

5.500 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

4.500 inches

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

Specification Or Standard:

1 type and d composition

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0