NSN 4820-00-289-1523

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-289-1523 Flow Control Device: Disk **Bonnet Type:** Exposed spring **Bonnet Attachment Method: Bolted Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 2220.0 pounds per hour **Bolt Hole Quantity:** 8 all ends **Maximum Operating Temp:** 775.0 degrees fahrenheit single response **Valve Operation Method:** Automatic or manual Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Features Provided:** Valve stem lock shield **Adjustable Pressure Range:** +25.0/+40.0 pounds per square inch **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Outside Diameter:** 6.625 inches all ends Thickness: 0.500 inches all ends **First Connection Face To Centerline Distance:** 5.500 inches **Bolt Hole Diameter:** 0.562 inches all ends **Second Connection Face To Centerline Distance:** 4.500 inches **Bolt Circle Diameter:** 5.500 inches all ends Flange Face Design:

Plain all ends

Material:

Stainless steel stem

NSN 4820-00-289-1523

Safety Relief Valve - Page 2 of 2



Media	For	Which	Designed
Steam	sing	le respo	onse

Style Designator:

Angle flanged ends

Specification Or Standard:

1 type and d composition

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0