

View Online at <https://aerobasegroup.com/nsn/4820-00-289-1789>

Pipe Size Accommodated:

0.500 inches 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Disk

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

4 2nd end

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) 1st end

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes 2nd end

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Valve stem lock shield

Thready Qty Per Inch (tpi):

14 1st end

Adjustable Pressure Range:

+91.0/+144.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch single response

Thread Size:

0.500 inches 1st end

Outside Diameter:

3.750 inches 2nd end

Thickness:

0.562 inches 2nd end

First Connection Face To Centerline Distance:

3.750 inches

Bolt Hole Diameter:

0.562 inches 2nd end

Second Connection Face To Centerline Distance:

1.812 inches

Bolt Circle Diameter:

2.625 inches 2nd end

Flange Face Design:

Raised straight 2nd end

Raised Face Height:

0.250 inches 2nd end

Raised Face Diameter:

2.000 inches 2nd end

Material:

Steel uns j03008 body

Material Specification:

Mil-s-15083 military specification single material response body

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

Thread Series Designator:

Npt 1st end

Furnished Items And Quantity:

1 sight gage

Specification Or Standard:

1 type and d composition

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-s-15083 spec.