NSN 4820-00-289-1809

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-289-1809

Pipe Size Accommodated:

0.750 inches 2nd end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Maximum Operating Temp:

406.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) 1st end

Valve Operation Method:

Automatic or manual

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Valve stem lock shield

Adjustable Pressure Range:

+16.0/+30.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch single response

Thread Size:

0.750 inches 2nd end

Material:

Steel stem

Material Specification:

Qq-c-390, alloyb5/d/ federal specification single material response body

Media For Which Designed:

Steam single response

Style Designator:

Angle

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

NSN 4820-00-289-1809

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

