## NSN 4820-00-289-1859

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Disk Loading Method:** 

**Bolt Hole Quantity:** 

**Maximum Operating Temp:** 

Piston

Spring

4 all ends



View Online at https://aerobasegroup.com/nsn/4820-00-289-1859

450.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+10.0/+40.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
4.875 inches all ends
Thickness:
0.062 inches all ends
First Connection Face To Centerline Distance:
3.500 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
3.500 inches
Bolt Circle Diameter:
3.500 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
2.000 inches all ends
Material:
Copper alloy
Media For Which Designed:
Fuel/oil, hydrocarbon single response

## NSN 4820-00-289-1859

Safety Relief Valve - Page 2 of 2



•		
StVID	l Jacian	ator.
OLYIC	Design	atoi.

Angle flanged ends

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0