NSN 4820-00-289-2009

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk Loading Method:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-289-2009

Spring
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.000 inches
Adjustable Pressure Range:
+18.0/+32.0 pounds per square inch
Maximum Operating Pressure:
100.0 pounds per square inch single response
Outside Diameter:
5.562 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
3.875 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
4.000 inches
Bolt Circle Diameter:
4.438 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy stem
Media For Which Designed:
Steam single response
Style Designator:
Angle flanged ends
Shelf Life:
N/a

NSN 4820-00-289-2009

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0