## NSN 4820-00-289-2098

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-289-2098

| Thread Direction:                            |
|--|
| Right-hand all ends                          |
| Flow Control Device:                         |
| Disk   |
| Disk Loading Method:                         |
| Spring                                       |
| Maximum Operating Temp:                      |
| 400.0 degrees fahrenheit single response     |
| Connection Style:                            |
| Plain, optional en (pipe) all ends           |
| Valve Operation Method:                      |
| Automatic                                    |
| Connection Type:                             |
| Threaded internal pipe all ends              |
| Features Provided:                           |
| Pressure tight outlet side                   |
| Adjustable Pressure Range:                   |
| +30.0/+40.0 pounds per square inch           |
| Maximum Operating Pressure:                  |
| 160.0 pounds per square inch single response |
| Thread Size:                                 |
| 0.750 inches all ends                        |
| Material:                                    |
| Nickel alloy flow control device             |
| Media For Which Designed:                    |
| Water, fresh single response                 |
| Style Designator:                            |
| Angle  |
| Thread Series Designator:                    |
| Npt all ends                                 |
| Shelf Life:                                  |
| N/a  |
| Unit Of Measure:                             |
|  |
| Demilitarization:                            |
| No   |
| Fiig:  |
| A046b0                                       |
|  |
|  |